



Military-Fasteners.com

P/N NAS5901-7

Description

Fastener Length: 7/16", Thread: 6-32, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS59017
Minimum Qty (MOQ):	40 EA
NSN:	5305-01-408-7073
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



* See page 2 for technical characteristics

P/N NAS5901-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.357 Inches Minimum And 0.440 Inches Maximum
Fastener Length:	0.440 Inches Nominal
Head Style:	Hexagon
Head Height:	0.080 Inches Minimum And 0.095 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp E4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams6322 Assn Std 2nd Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response
Thread Surface Finish:	32.0 Microinches
Thread Series Designator:	Unjc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5901-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.