

**Description**

length: 3/4", thread: 8-32, hex head screw - full thread - cadmium plated alloy steel - tri-wing recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS590212
Minimum Qty (MOQ):	10
NSN:	5305-01-338-9380
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS5902-12 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.688 Inches Minimum And 0.750 Inches Maximum
<b>Fastener Length:</b>	0.750 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.096 Inches Minimum And 0.110 Inches Maximum
<b>Width Between Flats:</b>	0.243 Inches Minimum And 0.251 Inches Maximum
<b>Internal Drive Style:</b>	Tri-wing Recess
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
<b>Screw Material:</b>	Steel Comp 4340 Or Steel Comp 8740
<b>Screw Surface Treatment:</b>	Cadmium And Chromate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas5902 Professional/Industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5902-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.