

Description

length: 1-1/8", thread: 10-32, hex head screw - full thread - cadmium plated alloy steel - tri-wing recess

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS590318
Minimum Qty (MOQ):	10
NSN:	5305-01-183-3285



P/N NAS5903-18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.125 Inches Nominal
Fastener Length:	1.062 Inches Minimum And 1.125 Inches Maximum
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.313 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Ams 6322 Assn Std 2nd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas5903 Professional/Industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5903-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.