

Description

Fastener Length: 2-", Thread: 10-32, Thread Length: 2-

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS590332
Minimum Qty (MOQ):	30 EA
NSN:	5305-01-304-2901
Schedule B:	7318.15.6080
ECCN:	9A991



P/N NAS5903-32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	2.000 Inches Maximum
Fastener Length:	2.000 Inches Nominal
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.313 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Ams 6322 Assn Std 2nd Material Response
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas5903 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5903-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.