

Description

length: 7/16", thread: 10-32, hex head screw - full thread - cadmium plated alloy steel - tri-wing recess

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS59037
Minimum Qty (MOQ):	10
NSN:	5305-01-183-3291



\* See page 2 for technical characteristics

## P/N NAS5903-7 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.438 Inches Nominal
<b>Fastener Length:</b>	0.408 Inches Minimum And 0.438 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.105 Inches Minimum And 0.120 Inches Maximum
<b>Width Between Flats:</b>	0.305 Inches Minimum And 0.313 Inches Maximum
<b>Internal Drive Style:</b>	Tri-wing Recess
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Comp 4340 Or Steel Comp 8740
<b>Screw Material Document And Classification:</b>	Mil-s-5000 Mil Spec 1st Material Response Or Ams 6322 Assn Std 2nd Material Response
<b>Screw Surface Treatment:</b>	Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas5903 Professional/Industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS5903-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.