

## **P/N NAS600-12**

## **Description**

- \*New call out is NAS600-12P\* Fastener Length: 3/4", Thread: 4-40, Thread Length: 3/4
- \* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

#### **Alternate Part Numbers**

#### NAS600-12P

SKU / Model: NAS60012

Minimum Qty (MOQ): 100

NSN: 5305-00-616-8080

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS600-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.700 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.750 Inches Nominal
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS600-12">https://military-fasteners.com/screws/machine+screws/NAS600-12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/NAS600-12">https://military-fasteners.com/screws/machine+screws/NAS600-12</a> and selecting the quantity you