

## **P/N NAS600-12B**

## **Description**

Fastener Length: 3/4", Thread: 4-40, Thread Length: 3/4

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS60012B

Minimum Qty (MOQ): 100

NSN: 5305-01-169-2902

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS600-12B Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.670 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.720 Inches Minimum And 0.750 Inches Maximum
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response
Screw Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response
Color:	Black
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas600 Professional/industrial Association Standard

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS600-12B">https://military-fasteners.com/screws/machine+screws/NAS600-12B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.