

P/N NAS600-22P

Military-Fasteners.com

#### Description

Fastener Length: 1-3/8", Thread: 4-40, Thread Length: 1-3/8

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

### **Additional Information**

SKU / Model:	NAS60022P
Minimum Qty (MOQ):	50
NSN:	5305-00-891-3459
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N NAS600-22P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.325 Inches Minimum And 1.375 Inches Maximum
Fastener Length:	1.375 Inches Nominal
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas600 Professional/industrial Association Standard

## How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/NAS600-22P</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.