

Description

Fastener Length: 7/16", Thread: 4-40, Thread Length: 7/16", NAS600 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6007B
Minimum Qty (MOQ):	50
NSN:	5305-00-834-6170
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS600-7B Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.360 Inches Minimum And 0.440 Inches Maximum
Fastener Length:	0.410 Inches Minimum And 0.440 Inches Maximum
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate And Chromium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec 1st Treatment Response Or Qq-p-416,ty 2 Cl 3 Fed Spec 2nd Treatment Response Or Bulletin 65-8-cd Assn Std 3rd Treatment Response
Thread Series Designator:	Unjc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS600-7B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.