

Description

length: 1/2, thread: 4-40, pan head, fully threaded, phillips recess, alloy steel, NAS600 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6008P
Minimum Qty (MOQ):	100
NSN:	5305-00-837-9925
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS600-8P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.953 Inches Minimum
Fastener Length:	3.203 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	1.265 Inches Minimum And 1.272 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.625 Inches
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Steel
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS600-8P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.