

## Description

Fastener Length: 1-39/64", Thread: 8-32, Thread Length: 1-39/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS6002U26
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-003-6824
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS6002U26 Specifications

<b>Thread Class:</b>	3a
<b>Thread Length:</b>	1.498 Inches Minimum And 1.620 Inches Maximum
<b>Fastener Length:</b>	1.560 Inches Minimum And 1.620 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.096 Inches Minimum And 0.110 Inches Maximum
<b>Width Between Flats:</b>	0.243 Inches Minimum And 0.251 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Screw Surface Treatment:</b>	Passivate
<b>Special Features:</b>	Tri-wing Recess Drive
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas6002 Professional/industrial Association Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6002U26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.