

Description

Fastener Length: 1-39/64", Thread: 8-32, Thread Length: 1-39/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6002U26
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-003-6824
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6002U26 Specifications

Thread Class:	3a
Thread Length:	1.498 Inches Minimum And 1.620 Inches Maximum
Fastener Length:	1.560 Inches Minimum And 1.620 Inches Maximum
Head Style:	Hexagon
Head Height:	0.096 Inches Minimum And 0.110 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Surface Treatment:	Passivate
Special Features:	Tri-wing Recess Drive
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas6002 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6002U26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.