

Description

Fastener Length: 11/16", Thread: 6-32, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS60111B
Minimum Qty (MOQ):	35 EA
NSN:	5305-00-855-3247
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS601-11B Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.598 Inches Minimum And 0.690 Inches Maximum
Fastener Length:	0.660 Inches Minimum And 0.690 Inches Maximum
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum And 32.0 Rockwell C Maximum
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-416,ty 2 Cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas601 Professional/Industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS601-11B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.