

**Description**


length: 3/4", thread: 6-32, pan head, fully threaded, philips recess, alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS60112B
Minimum Qty (MOQ):	100
NSN:	5305-01-560-7096
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS601-12B Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.750 Inches Maximum
<b>Fastener Length:</b>	0.750 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.256 Inches Minimum And 0.270 Inches Maximum
<b>Head Height:</b>	0.087 Inches Minimum And 0.097 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Screw Material:</b>	Steel Comp 4140 Or Steel Comp 4340
<b>Screw Material Document And Classification:</b>	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 2nd Material Response
<b>Screw Surface Treatment:</b>	Cadmium
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas 601 Professional/Industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS601-12B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.