



★ FASTENERS

Military-Fasteners.com

**P/N NAS601-14P**

## Description

length: 7/8", thread: 6-32, pan head, fully threaded, philips recess, alloy steel, NAS601 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS60114P                                 |
| Minimum Qty (MOQ):      | 100                                       |
| NSN:                    | 5305-00-840-5302                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS601-14P Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3a   |
| <b>Thread Direction:</b>                                    | Right-hand   |
| <b>Thread Length:</b>                                       | 0.788 Inches Minimum And 0.880 Inches Maximum  |
| <b>Fastener Length:</b>                                     | 0.850 Inches Minimum And 0.880 Inches Maximum  |
| <b>Head Style:</b>  | Pan No. 2  |
| <b>Head Diameter:</b>                                       | 0.256 Inches Minimum And 0.270 Inches Maximum  |
| <b>Head Height:</b>   | 0.087 Inches Minimum And 0.097 Inches Maximum  |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1  |
| <b>Nominal Thread Diameter:</b>                             | 0.138 Inches   |
| <b>Thread Quantity Per Inch:</b>                            | 32   |
| <b>Minimum Tensile Strength:</b>                            | 160000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                                     | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum                                  |
| <b>Screw Material:</b>                                      | Steel Comp 4037 Or Steel Comp 8630   |
| <b>Screw Material Document And Classification:</b>          | Ams 6300 Assn Std 1st Material Response Or Mil-s-6050 Mil Spec 2nd Material Response |
| <b>Screw Surface Treatment:</b>                             | Cadmium And Chromate   |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response                                |
| <b>Thread Series Designator:</b>                            | Unjc   |
| <b>Specification/standard Data:</b>                         | 80205-nas 601 Professional/industrial Association Standard                           |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS601-14P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.