

# P/N NAS601-16P

Military-Fasteners.com

#### Description


length: 1", thread: 6-32, pan head, fully threaded, philips recess, alloy steel, NAS601 series screw

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS60116P
Minimum Qty (MOQ):	100
NSN:	5305-00-995-2120
Schedule B:	7318.15.4000
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS601-16P Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.938 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	1.000 Inches Nominal
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas601 Professional/industrial Association Standard

### How to Order

Order this machine screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/NAS601-16P</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.