

Description

NAS601-6B Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS6016B
Minimum Qty (MOQ):	100
NSN:	5305-00-821-5193
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS601-6B Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Fastener Length:	0.375 Inches Nominal
Head Style:	Pan
Head Diameter:	0.256 Inches Minimum And 0.270 Inches Maximum
Head Height:	0.087 Inches Minimum And 0.097 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment:	Cadmium
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas601 Professional/Industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS601-6B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.