



★ FASTENERS

Military-Fasteners.com

P/N NAS602-12

Description

Fastener Length: 3/4", Thread: 8-32, Thread Length: 11/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS60212
Minimum Qty (MOQ):	100
NSN:	5305-00-995-2123
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS602-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.688 Inches Minimum And 0.750 Inches Maximum
Fastener Length:	0.750 Inches Nominal
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Type 2,class 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS602-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.