

Description


length: 3/4", thread: 8-32, pan head, fully threaded, philips recess, alloy steel, NAS602 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS60212P |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-995-2123 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS602-12P Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.688 Inches Minimum And 0.750 Inches Maximum |
| Fastener Length: | 0.750 Inches Nominal |
| Head Style: | Pan |
| Head Diameter: | 0.306 Inches Minimum And 0.322 Inches Maximum |
| Head Height: | 0.105 Inches Minimum And 0.115 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum |
| Screw Material: | Steel Comp 8630 |
| Screw Material Document And Classification: | Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response |
| Screw Surface Treatment: | Cadmium And Chromate |
| Screw Surface Treatment Document And Classification: | Qq-p-416 Type 2,class 3 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unjc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS602-12P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.