

Description


length: 13/16", thread: 10-32, pan head, fully threaded, philips recess, alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS60213P
Minimum Qty (MOQ):	100
NSN:	5305-00-932-5695
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS602-13P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum And 0.812 Inches Maximum
Fastener Length:	0.781 Inches Minimum And 0.812 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Assn Std Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS602-13P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.