

# P/N NAS602-56P

## **Description**

Fastener Length: 5-63/64", Thread: 8-32, Thread Length: 1-3/4", pan head

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS60256P

Minimum Qty (MOQ): 5

NSN: 5305-00-078-0185

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS602-56P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.750 Inches Nominal
Fastener Length:	5.910 Inches Minimum And 6.000 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel
Screw Material Document And Classification:	Mil-s-7839 Mil Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,ty2,cl3 Fed Spec Single Treatment Response
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas602 Professional/industrial Association Standard

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS602-56P">https://military-fasteners.com/screws/machine+screws/NAS602-56P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/NAS602-56P">https://military-fasteners.com/screws/machine+screws/NAS602-56P</a> and selecting the quantity you