

**Description**

Fastener Length: 5-63/64", Thread: 8-32, Thread Length: 1-3/4", pan head

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS60256P                                 |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5305-00-078-0185                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS602-56P Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>                                    | Right-hand  |
| <b>Thread Length:</b>                                       | 1.750 Inches Nominal                                      |
| <b>Fastener Length:</b>                                     | 5.910 Inches Minimum And 6.000 Inches Maximum             |
| <b>Head Style:</b>  | Pan No. 2   |
| <b>Head Diameter:</b>                                       | 0.306 Inches Minimum And 0.322 Inches Maximum             |
| <b>Head Height:</b>   | 0.105 Inches Minimum And 0.115 Inches Maximum             |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1                                       |
| <b>Nominal Thread Diameter:</b>                             | 0.164 Inches  |
| <b>Thread Quantity Per Inch:</b>                            | 32  |
| <b>Minimum Tensile Strength:</b>                            | 160000 Pounds Per Square Inch                             |
| <b>Hardness Rating:</b>                                     | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum       |
| <b>Screw Material:</b>                                      | Steel   |
| <b>Screw Material Document And Classification:</b>          | Mil-s-7839 Mil Spec Single Material Response              |
| <b>Screw Surface Treatment:</b>                             | Cadmium And Chromate                                      |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,ty2,cl3 Fed Spec Single Treatment Response       |
| <b>Thread Series Designator:</b>                            | Unjc  |
| <b>Specification/standard Data:</b>                         | 80205-nas602 Professional/industrial Association Standard |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS602-56P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.