



★ FASTENERS

Military-Fasteners.com

P/N NAS602-8

Description

length: 1/2", thread: 8-32, pan head, fully threaded, philips recess, alloy steel cadmium ii plating, NAS602 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6028
Minimum Qty (MOQ):	100
NSN:	5305-01-350-4928
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS602-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Nominal
Fastener Length:	0.500 Inches Nominal
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type Iii
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp 4140
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas602-8 Professional/Industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS602-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.