

Description

Fastener Length: 35/64", Thread: 8-32, Thread Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6029B
Minimum Qty (MOQ):	50 EA
NSN:	5305-00-078-0186
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS602-9B Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.478 Inches Minimum And 0.560 Inches Maximum
Fastener Length:	0.530 Inches Minimum And 0.560 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel
Screw Material Document And Classification:	Mil-s-7839 Mil Spec Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response
Color:	Black
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas602 Professional/Industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS602-9B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.