

Description

length: 5/8", thread: 10-32, pan head, fully threaded, philips recess, alloy steel, NAS603 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS60310P
Minimum Qty (MOQ):	100
NSN:	5305-00-841-9825
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS603-10P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.563 Inches Minimum And 0.625 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Assn Std 1st Material Response Or Mil-s-5000 Assn Std 2nd Material Response Or Mil-s-6049 Assn Std 3rd Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-b-416,ty 2,cl 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS603-10P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.