

Description

Fastener Length: 1-7/64", Thread: 10-32, Thread Length: 1-7/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS60319
Minimum Qty (MOQ):	50 EA
NSN:	5305-01-467-8134
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS603-19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.090 Inches Minimum And 1.112 Inches Maximum
Fastener Length:	1.090 Inches Minimum And 1.112 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.1900 Inches
Thread Quantity Per Inch:	32
Screw Material:	Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS603-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.