

Description

Fastener Length: 1-3/16", Thread: 10-32, Thread Length: 1-3/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS60319P
Minimum Qty (MOQ):	50
NSN:	5305-00-450-8015
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS603-19P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.066 Inches Minimum And 1.188 Inches Maximum
Fastener Length:	1.128 Inches Minimum And 1.188 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response
Screw Surface Treatment:	Cadmium And Chromate
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas603 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS603-19P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.