

Description

Fastener Length: 1-1/4", Hole Diameter: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS60321
Minimum Qty (MOQ):	20 EA
NSN:	5305-01-534-4283
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS603-21 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.250 Inches Nominal
Head Style:	Dee
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Hole Diameter:	0.190 Inches Maximum
End Item Identification:	1520-01-106-9519
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Askewed Head Angle:	0.010 Radians Minimum And 0.020 Radians Maximum
Part Name Assigned By Controlling Agency:	Screw Machine-aircraft, Pan Head, Cruiform Recess Full
Screw Material:	Steel Comp 414 Or Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Std All Material Responses Or Mil-s-5000 Mil Std All Material Responses Or Mil-s-6049 Mil Std All Material Responses
Head Hole Configuration Style:	Round
Special Features:	Point Is Flat And Chamfered
Thread Series Designator:	Unjf
Specification/standard Data:	80205 - Nas603 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS603-21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.