

P/N NAS603-21

Description

Fastener Length: 1-1/4", Hole Diameter: 1/4"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS60321

Minimum Qty (MOQ): 20 EA

NSN: 5305-01-534-4283

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS603-21 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	1.250 Inches Nominal
Head Style:	Dee
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Hole Diameter:	0.190 Inches Maximum
End Item Identification:	1520-01-106-9519
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Askewed Head Angle:	0.010 Radians Minimum And 0.020 Radians Maximum
Part Name Assigned By Controlling Agency:	Screw Machine-aircraft, Pan Head, Cruiform Recess Full
Screw Material:	Steel Comp 414 Or Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Std All Material Responses Or Mil-s-5000 Mil Std All Material Responses Or Mil-s-6049 Mil Std All Material Responses
Head Hole Configuration Style:	Round
Special Features:	Point Is Flat And Chamfered
Thread Series Designator:	Unjf
Specification/standard Data:	80205 - Nas603 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS603-21 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.