

## **P/N NAS604-11P**

## **Description**

Fastener Length: 43/64", Thread: 1/4-28, Thread Length: 19/32

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS60411P

Minimum Qty (MOQ): 50

NSN: 5305-00-150-0825

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS604-11P Specifications

Thread Class:	20
Inread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.588 Inches Minimum And 0.690 Inches Maximum
Fastener Length:	0.659 Inches Minimum And 0.690 Inches Maximum
Head Style:	Pan
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740
Screw Material Document And	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material
Classification:	Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas604 Professional/industrial Association Standard

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS604-11P">https://military-fasteners.com/screws/machine+screws/NAS604-11P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.