

# **P/N NAS604-12**

## **Description**

Fastener Length: 3/4", Thread: 1/4-28, Thread Length: 3/4

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS60412

Minimum Qty (MOQ): 50

NSN: 5305-01-570-7502

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel









# **P/N NAS604-12 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Nominal
Fastener Length:	0.750 Inches Nominal
Head Style:	Pan
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	1520-01-355-8250 Helicopter, Attack
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Screw, Machine, Pan Head
Screw Material:	Steel Comp 4140
Screw Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response
Head Surface Treatment:	Cadmium
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416, Type Ii. Class 2 Fed Spec Single Treatment Response
Thread Series Designator:	Unjef

### **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS604-12">https://military-fasteners.com/screws/machine+screws/NAS604-12</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.