

Description

Fastener Length: 0-63/64", Thread: 1/4-28, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS60416
Minimum Qty (MOQ):	55 EA
NSN:	5305-00-718-9470
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS604-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.899 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	0.970 Inches Minimum And 1.000 Inches Maximum
Head Style:	Pan
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-562 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416,ty 1,c 3 Fed Spec Single Treatment Response
Special Features:	Fleet Ballistic Missile Quality As Identified By Quality Control No.posp913093
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas604 Professional/industrial Association Standard
Departure From Cited Designator:	As Modified By Special Features

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS604-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.