

**Description**

NAS604-18 Machine Screw

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS60418                                  |
| Minimum Qty (MOQ):      | 25  |
| NSN:                    | 5305-00-558-3731                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS604-18 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>                                    | Right-hand  |
| <b>Thread Length:</b>                                       | 0.989 Inches Minimum And 1.120 Inches Maximum   |
| <b>Fastener Length:</b>                                     | 1.060 Inches Minimum And 1.120 Inches Maximum   |
| <b>Head Style:</b>  | Pan   |
| <b>Head Diameter:</b>                                       | 0.473 Inches Minimum And 0.492 Inches Maximum   |
| <b>Head Height:</b>   | 0.162 Inches Minimum And 0.175 Inches Maximum   |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1   |
| <b>Nominal Thread Diameter:</b>                             | 0.250 Inches  |
| <b>Thread Quantity Per Inch:</b>                            | 28  |
| <b>Minimum Tensile Strength:</b>                            | 160000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                                     | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum   |
| <b>Screw Material:</b>                                      | Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 8740  |
| <b>Screw Material Document And Classification:</b>          | Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response |
| <b>Screw Surface Treatment:</b>                             | Cadmium   |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,ty 1,cl 3 Fed Spec Single Treatment Response   |
| <b>Thread Series Designator:</b>                            | Unjf  |
| <b>Specification/standard Data:</b>                         | 80205-nas604 Professional/industrial Association Standard   |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS604-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.