

Description

Fastener Length: 1-1/2", Thread: 1/4-28, Thread Length: 1-1/2", pan head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS60424P
Minimum Qty (MOQ):	50
NSN:	5305-00-919-5133
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS604-24P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.429 Inches Minimum And 1.500 Inches Maximum
Fastener Length:	1.500 Inches Nominal
Head Style:	Pan
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.173 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Screw Material:	Steel Comp 8630
Screw Material Document And Classification:	Mil-s-6050 Mil Spec Single Material Response Or An-s-9 Mil Std Single Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS604-24P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.