

## **P/N NAS604-50P**

## **Description**

Fastener Length: 3-1/8", Thread: 1/4-28, Thread Length: 1-3/4

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS60450P

Minimum Qty (MOQ):

NSN: 5305-01-452-9260


Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N NAS604-50P Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.750 Inches Minimum
Fastener Length:	3.035 Inches Minimum And 3.125 Inches Maximum
Head Style:	Pan
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Screw Material:	Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740
Screw Surface Treatment Document And Classification:	Qq-p-416, Type 2, Class 2 Fed Spec 1st Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas604 Professional/industrial Association Standard

### **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS604-50P">https://military-fasteners.com/screws/machine+screws/NAS604-50P</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outher to complete your order.