

Description

Fastener Length: ", Thread: 1/4-24, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS60510
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-468-5927
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS605-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.620 Inches Nominal
Fastener Length:	0.620 Inches Nominal
Head Style:	Pan
Head Diameter:	0.594 Inches Minimum And 0.615 Inches Maximum
Head Height:	0.203 Inches Minimum And 0.218 Inches Maximum
Internal Drive Style:	Cross Recess Type Iii
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Thread Pitch In Millimeters:	1.0
External Thread Tolerance Class:	3a
Screw Material:	Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Or Mil-c-5000 Mil Spec 2nd Material Response Or Mil-s-6049 Mil Spec 3rd Material Response
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS605-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.