

## Description


Fastener Length: 7/8", Thread: 1/4-24, Thread Length: 7/8", NAS605 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS60514P                                 |
| Minimum Qty (MOQ):      | 50  |
| NSN:                    | 5305-01-006-2058                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS605-14P Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>                                    | Right-hand  |
| <b>Thread Length:</b>                                       | 0.766 Inches Minimum And 0.880 Inches Maximum             |
| <b>Fastener Length:</b>                                     | 0.849 Inches Minimum And 0.880 Inches Maximum             |
| <b>Head Style:</b>  | Pan   |
| <b>Head Diameter:</b>                                       | 0.594 Inches Minimum And 0.615 Inches Maximum             |
| <b>Head Height:</b>   | 0.203 Inches Minimum And 0.218 Inches Maximum             |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1                                       |
| <b>Nominal Thread Diameter:</b>                             | 0.312 Inches  |
| <b>Thread Quantity Per Inch:</b>                            | 24  |
| <b>Minimum Tensile Strength:</b>                            | 160000 Pounds Per Square Inch                             |
| <b>Hardness Rating:</b>                                     | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum       |
| <b>Screw Material:</b>                                      | Steel Comp 4340 Or Steel Comp 4140 Or Steel Comp 8740     |
| <b>Screw Surface Treatment:</b>                             | Cadmium And Chromate                                      |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2 Cl 2 Fed Spec All Treatment Responses       |
| <b>Thread Series Designator:</b>                            | Unjf  |
| <b>Specification/standard Data:</b>                         | 80205-nas605 Professional/industrial Association Standard |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS605-14P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.