

Description

Machine Screw part number

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------|
| SKU / Model: | NAS607310P |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5315-00-806-2136 |
| ECCN: | EAR99 |
| National Motor Freight: | 063520, Waveguide In Boxes / Crates |



* See page 2 for technical characteristics

P/N NAS607-3-10P Specifications

| | |
|--|---|
| First End Style: | Chamfered |
| Second End Style: | Radius |
| Pin Overall Length: | 1.250 Inches Nominal |
| Pin Overall Diameter: | 0.1880 Inches Nominal |
| Second End Corner Radius: | 0.051 Inches Nominal |
| First End Taper Length: | 0.019 Inches Nominal |
| Features Provided: | Casehardened |
| Second End Relationship With First End: | Not Identical |
| Hardness Rating: | 50.0 Rockwell C Minimum Overall And 64.0 Rockwell C Maximum Overall |
| First End Taper Angle: | 5.0 Degrees Nominal |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS607-3-10P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.