



Military-Fasteners.com

P/N NAS608-3H12

Description

Fastener Length: 49/64", Hole Diameter: 1/32", Thread: 10-32, Head Width: 5/32", Thread Length: 49/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6083H12
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-058-5087
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS608-3H12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.770 Inches Maximum
Fastener Length:	0.740 Inches Minimum And 0.770 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.306 Inches Minimum And 0.313 Inches Maximum
Head Height:	0.185 Inches Minimum And 0.190 Inches Maximum
Hole Diameter:	0.037 Inches Nominal
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.156 Inches Minimum And 0.158 Inches Maximum
Hole Quantity:	2
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 45.0 Rockwell C Maximum Overall
Minimum Yield Strength:	130000 Pounds Per Square Inch
Hole Configuration Style:	Round
Material:	Steel Overall
Material Document And Classification:	66 Fed Std Single Material Response Overall
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS608-3H12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.