

Description

Fastener Length: 15/16", Thread: 10-32, Thread Length: 15/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6103U15
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-183-3300
Schedule B:	7318.15.6080
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS6103U15 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.910 Inches Minimum And 0.940 Inches Maximum
Fastener Length:	0.910 Inches Minimum And 0.940 Inches Maximum
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.313 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Screw Material:	Titanium Alloy
Screw Material Document And Classification:	Ams4928 Assn Std Single Material Response Or Ams4967 Assn Std Single Material Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6103 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6103U15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.