

## P/N NAS6103U17

### **Description**

Fastener Length: 1-1/16", Thread: 10-32, Thread Length: 1-1/16"

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS6103U17
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-183-3302
Schedule B:	8108.90.3060
ECCN:	EAR99



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS6103U17 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.032 Inches Minimum And 1.062 Inches Maximum
Fastener Length:	1.032 Inches Minimum And 1.062 Inches Maximum
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.313 Inches Maximum
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Screw Material:	Titanium Alloy
Screw Material Document And Classification:	Ams4928 Assn Std Single Material Response Or Ams4967 Assn Std Single Material Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6103 Professional/industrial Association Standard

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6103U17">https://military-fasteners.com/bolts/shear+bolts/NAS6103U17</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6103U17">https://military-fasteners.com/bolts/shear+bolts/NAS6103U17</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6103U17">https://military-fasteners.com/bolts/shear+bolts/NAS6103U17</a> and selecting the quantity you want then click "add to cart".