

Description

Fastener Length: 1-3/8", Thread: 10-32, Thread Length: 1-3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS6103U22 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-183-9953 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS6103U22 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.320 Inches Minimum And 1.380 Inches Maximum |
| Fastener Length: | 1.320 Inches Minimum And 1.380 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.105 Inches Minimum And 0.120 Inches Maximum |
| Width Between Flats: | 0.305 Inches Minimum And 0.313 Inches Maximum |
| Internal Drive Style: | Tri-wing Recess |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Screw Material: | Titanium Alloy |
| Screw Material Document And Classification: | Ams4928 Assn Std Single Material Response Or Ams4967 Assn Std Single Material Response |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6103 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6103U22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.