

## **P/N NAS617-6**

## **Description**

tubing outer diameter: 3/8", preformed packing, threaded tube fitting boss, NAS617 series o-ring

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS6176

Minimum Qty (MOQ): 25

NSN: 5331-00-576-9925

ECCN: EAR99

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS617-6 Specifications**

Cross-sectional Height:	0.075 Inches Minimum And 0.081 Inches Maximum
Center Hole Diameter:	0.463 Inches Minimum And 0.473 Inches Maximum
Material:	Rubber Butadiene-acrylonitrile Class Nbr

## **How to Order**

Order this o-ring from our inventory online by visiting <a href="https://military-fasteners.com/o\_rings/NAS617-6">https://military-fasteners.com/o\_rings/o\_rings/NAS617-6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/NAS617-6">https://military-fasteners.com/o\_rings/o\_rings/NAS617-6</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/o\_rings/NAS617-6">https://military-fasteners.com/o\_rings/O\_rings/NAS617-6</a> and selecting the quantity you want then click "add to cart".