

Description

diameter: 0.1380", thickness 0.016", NAS620 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6206L
Minimum Qty (MOQ):	100
NSN:	5310-00-616-6822
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N NAS620-6L Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.151 Inches Minimum And 0.161 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Center Hole Shape Style:	Round
Thickness:	0.016 Inches Nominal
Overall Diameter:	0.262 Inches Minimum And 0.282 Inches Maximum
End Item Identification:	Support Equipment, B-52 Aircraft;test Consoles, Mini-space;communications Terminal, Satellite An/gsc-39(v)1;aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130);support Equipment, B-1 Aircraft;test Station, Oq-290(v)msn;missile, Advanced Medium Range Air-to-air (amraam)/aim120a;missile, Tomahawk;missile,air-to-air, Phoenix (aim-54);support Equipment, F-15 Aircraft;lpd-17 Class Amphibious Transport Dock;missile, All-weather Anti-ship, Harpoon (agm-84).
Material:	Steel Overall
Material Document And Classification:	Qq-s-698 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS620-6L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.