

Description

length: 0.385", grip: 0.062", thread: 10-32, hex head, tension, short thread, cadmium plated alloy steel, NAS6203 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

[NAS1103-1](#)

SKU / Model:	NAS62031
Minimum Qty (MOQ):	50
NSN:	5306-01-369-3327
Schedule B:	7318.15.2095
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6203-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.370 Inches Minimum And 0.400 Inches Maximum
Head Style:	Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.052 Inches Minimum And 0.072 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	16000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material:	Steel Comp E4340 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Fed Spec 1st Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6203 Professional/Industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6203-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.