

Description

length: 0.948", grip: 0.625", thread: 10-32, hex head, drilled shank, tension, short thread, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS620310D
Minimum Qty (MOQ):	10
NSN:	5306-01-141-6645
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6203-10D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.933 Inches Minimum And 0.963 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Thread Quantity Per Inch:	32
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6203-10D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.