

Description

Fastener Length: 1", Hole Diameter: 3/16", Thread: 10-32, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS620311H
Minimum Qty (MOQ):	5
NSN:	5306-01-536-2155
Schedule B:	7318.15.8085
ECCN:	EAR99



P/N NAS6203-11H Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	1.011 Inches Nominal
Head Style:	Hexagon
Head Height:	0.090 Inches Minimum And 0.105 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Hole Diameter:	0.180 Inches Minimum And 0.200 Inches Maximum
Grip Diameter:	0.1845 Inches Minimum And 0.1850 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.688 Inches Nominal
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Hole Configuration Style:	Hexagon Longitudinal Hole
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Ams6349 Assn Std Single Material Response Overall Or Ams6484 Assn Std Single Material Response Overall Or Ams6332 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6203-11H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.