



★ FASTENERS

Military-Fasteners.com

**P/N NAS6203-11H**

## Description

Fastener Length: 1", Hole Diameter: 3/16", Thread: 10-32, Thread Length: 5/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS620311H
Minimum Qty (MOQ):	5
NSN:	5306-01-536-2155
Schedule B:	7318.15.8085
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS6203-11H Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	1.011 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.090 Inches Minimum And 0.105 Inches Maximum
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Hole Diameter:</b>	0.180 Inches Minimum And 0.200 Inches Maximum
<b>Grip Diameter:</b>	0.1845 Inches Minimum And 0.1850 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.688 Inches Nominal
<b>Hole Quantity:</b>	1
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	32
<b>Hole Configuration Style:</b>	Hexagon Longitudinal Hole
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Ams6349 Assn Std Single Material Response Overall Or Ams6484 Assn Std Single Material Response Overall Or Ams6332 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6203-11H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.