

P/N NAS6203-14Y

Military-Fasteners.com

Description

Fastener Length: 1-13/64", Thread: 10-32, Thread Length: 11/32

* Manufacturer certifications are shipped with your order $\underline{\mathsf{FREE}}$ of charge

Order this part online

Additional Information

| SKU / Model: | NAS620314Y |
|-------------------------|---|
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-147-4882 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS6203-14Y Specifications

| Thread Class: | 3a |
|---|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.298 Inches Minimum And 0.348 Inches Maximum |
| Fastener Length: | 1.183 Inches Minimum And 1.213 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.110 Inches Minimum And 0.125 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Shoulder Diameter: | 0.2172 Inches Minimum First Shoulder And 0.2182 Inches Maximum First Shoulder |
| Shoulder Length: | 0.865 Inches Minimum First Shoulder And 0.885 Inches Maximum First Shoulder |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Shoulder Shape: | Round First Shoulder |
| Material: | Steel Comp E4340 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6203 Professional/industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6203-14Y</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.