

**Description**

length: 0.448", grip: 0.125", thread: 10-32, hex head, tension, short thread, cadmium plated alloy steel, NAS6203 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS62032
Minimum Qty (MOQ):	100
NSN:	5306-01-055-3789
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS6203-2 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.298 Inches Minimum And 0.348 Inches Maximum
<b>Fastener Length:</b>	0.433 Inches Minimum And 0.463 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.110 Inches Minimum And 0.125 Inches Maximum
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Grip Diameter:</b>	0.1885 Inches Minimum And 0.1895 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.115 Inches Minimum And 0.135 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6203 Professional/industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6203-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.